



4 MegaPixel WDR Bullet Camera with Fixed Lens



IP-B14FC


Features

- 1/3" 4Megapixel progressive scan CMOS
- H.264 & MJPEG triple-stream encoding
- Smart Detection supported
- Max 20fps@4M(2560×1440) & 25/30fps@3M(2304×1296)
- WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, Snappy Universal CMS
- 3.6mm fixed lens (6mm optional)
- Max. IR LEDs Length 40m
- IP67, PoE



Dimensions (mm)

Accessory (optional)



Technical Specifications

Model		IP-B14FC	
Camera			
Image Sensor		1/3" 4Megapixel progressive scan CMOS	
Effective Pixels		2688(H)x1520(V)	
Scanning System		Progressive	
Electronic Shutter Speed		Auto/Manual, 1/3(4)~1/100000s	
Min. Illumination		0.01Lux/F1.4(Color); 0Lux/F1.4(IR on)	
S/N Ratio		More than 50dB	
Video Output		N/A	
Camera Features			
Max. IR LEDs Length		40m	
Day/Night		Auto(ICR) / Color / B/W	
Backlight Compensation		BLC / HLC /WDR(120dB)	
White Balance		Auto/Sunny/Night/Outdoor/Customized	
Gain Control		Auto/Manual	
Noise Reduction		3D	
Privacy Masking		Up to 4 areas	
Lens			
Focal Length		3.6mm (6mm optional)	
Max Aperture		F2.1(F2.0)	
Focus Control		Manual	
Angle of View		H:84°(56°)	
Lens Type		Fixed lens	
Mount Type		Board-in Type	
Video			
Compression		H.264/H.264H/H.264B/MJPEG	
Resolution		4M(2688x1520)/4M(2560x1440)/3M(2304x1296)/1080P (1920x108 0)/1.3M(1280× 960)/720P(1280× 720)/D1(704× 576/704× 480)/ CIF(3 52× 288/352× 240)	
Frame Rate	Main Stream	4M(1~20fps)/3M(1~25/30fps)	
	Sub Stream	D1/CIF(1 ~ 25/30fps)	
	Third Stream	720P(1-20fps)	
Bit Rate		H.264: 32K ~ 10Mbps	
Corridor mode		Support	
Audio			
Compression		N/A	
Interface		N/A	
Smart Function			
Smart detection	Tripwire		
	Intrusion		
	Abandoned/Missing		
	Scene Change		
	Audio detect		
	Face detect		
Network			
Ethernet		RJ-45 (10/100Base-T)	
Wi-Fi		N/A	
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x	
ONVIF		ONVIF,PSIA,CGI	
Max. User Access		20users	
Smart Phone		iPhone, iPad, Android, Windows Phone	
Auxiliary Interface			
Memory Slot		N/A	
RS485		N/A	
Alarm		N/A	
PIR Sensor Range		N/A	
General			
Power Supply		DC12V, PoE (802.3af)	
Power Consumption		< 6W	
Working Environment		-30°C~+60°C, Less than 95% RH	
Ingress Protection		IP67	
Vandal Resistance		N/A	
Dimensions		70mm×70mm× 180mm	
Weight		0.4kg(0.528kg with packaging)	

Mailing Address

VOSTOK Trading L.L.C,

304, 3rd Floor, Al Tawhidi Building,
Khaled Bin Waleed Road,
P.O. Box: 27106 - Dubai,
UNITED ARAB EMIRATES.

www.snappy.ae

Contact Details

Tel : (+971 4) 3558816
Fax : (+971 4) 3558817
Email : sales1@snappy.ae /
sales2@snappy.ae /
sales3@snappy.ae