

1.3MP HD WDR Network Vandal-proof IR Dome Camera


IP-D2P103MVFWC



Features

- 1/3" 1.3Megapixel progressive scan CMOS
- Support H.264&MJPEG dual codec
- 25/30fps@1.3M(1080× 960)
- Smart Detection supported
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, Snappy Universal CMS
- 2.7mm ~12mm motorized lens
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 50m
- Micro SD memory, IP67, IK10, PoE

Dimensions (mm)



Technical Specifications

Model		IP-D2P103MVFWC	
Camera			
Image Sensor		1/3" 1.3Megapixel progressive scan CMOS	
Effective Pixels		1080(H) x 960(V)	
Scanning System		Progressive	
Electronic Shutter Speed		Auto/Manual, 1/ 3(4)~1/1000 00s	
Min. Illumination		0.01Lux/F1.4(Color) ; 0Lux/F1.4(IR on)	
S/N Ratio		More than 50dB	
Video Output		1 port	
Camera Features			
Max. IR LEDs Length		50m	
Day/Night		Auto(ICR) / Color / B/W	
Backlight Compensation		BLC / HLC / WDR (120dB)	
White Balance		Auto/Sunny/Night/Outdoor/Customized	
Gain Control		Auto/Manual	
Noise Reduction		3D	
Privacy Masking		Up to 4 areas	
Lens			
Focal Length		2.7mm~12mm	
Max Aperture		F1.4	
Focus Control		Motorized	
Angle of View		H: 90°~29°	
Lens Type		Motorized/ Auto Iris(DC)	
Mount Type		Board -in Type	
Video			
Compression		H.264 /H.264H/ H.264B/ MJPEG	
Resolution		1.3M (1280×960)/720P(1280×720)/D1(704×576 /704×480)/CIF(352×288 /352×240)	
Frame Rate	Main Stream	1.3M /720P (1 ~ 25/30fps)	
	Sub Stream	D1/CIF(1 ~ 25/30fps)	
	Third Stream	720P(1 ~ 14/7fps)	
Bit Rate		H.264: 32K ~ 10M bps	
Corridor Mode		Support	
Audio			
Compression		G.711a/ G.711u/ AAC	
Interface		1/1 channel In/Out	
Smart Function			
Smart detection		Tripwire	
		Intrusion	
		Abandoned/Missing	
		Scene Change	

	Audio detect
	Face detect
Network	
Ethernet	RJ-45 (10/100Base -T)
Wi-Fi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
ONVIF	ONVIF, PSIA, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 128 GB
RS485	N/A
Alarm	1/1 channel In/Out
PIR Sensor Range	N/A
General	
Power Supply	DC12V(AC 24V optional), PoE (802.3af)
Power Consumption	Max 10 W (with IR on, motorized lens working)
Working Environment	-30°C~+60°C, Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10
Dimensions	Φ 159mm×117.9mm
Weight	0.8Kg

Accessory (Optional)



Mailing Address

Snappy
Orlyplein 85
1043 DS Amsterdam
The Netherlands

Contact Details

Tel : +31 (0) 204037397
Fax : +31 (0) 204037310
Email : sales1@snappyeurope.com
sales2@snappyeurope.com
Website : www.snappyeurope.com